

Accessories and spare parts



	FlowMeter 10 - 100	FlowMeter 100 - 700
Display unit (L/W/H) 62/62/22 mm	sensor (L/W/H) 80/50/26 mm	sensor (L/W/H) 97/50/33 mm
Flow range	10 - 100 l/h	100 - 700 l/h
Flow deviation	± max. 5 %	
Operating pressure	max. 8.6 bar	
Pressure loss	with flow of 100 l/h: < 0.3 bar	with flow of 700 l/h: < 1.1 bar
Water intake temperature	4 - 30 °C	
Cable length	max. 1.5 m	
Inlet connection	G 3/8" Union nut	G 3/4" with o-ring seal
Outlet connection	G 3/8"	G 3/4" union nut
Order number	1033041	1033042

Remote display		
Measurements (L/W/H)	138 / 48 / 103 mm	
Cable length PURITY remote display	ca. 2 m	
Cable length remote display - machine	max. 10 m	
Powersupply	by battery of the MDU display unit	
Switched current	max. 50 m ADC	
Degree of protection Remote Display (only when wall-mounted)	IPX4	
Screw size cover	Torx T6	
Order number	274100	

The remote display module provides convenience and flexibility: fit the handy extension kit in a visible location on the wall and you have all operating parameters in sight at all times.

Calculates the residual capacity of the filter after the relevant filter capacity is set by recording the volumetric flow. Installed horizontally. FlowMeter is now equipped with a Velcro adhesive spot for comfortable fixation.



Pressure vessel lid without display unit	Order number	
PURITY PURITY 450 / 600 Quell ST	272100	
PURITY 1200 Steam	1001461	
PURITY 1200 Clean / Clean Extra	273825	



Pressure vessel lid with display unit	Order number	
PURITY 450 / 600 Quell ST	272000	
PURITY 1200 Quell ST	272400	
PURITY 450 / 600 Steam	1004331	
PURITY 1200 Steam	1004328	



Display		
Order number	321300	
Digital indication device to be fitted to the pressure vessel lid electronically or fitted as a remote display at eye level.		



Pressure vessel PURITY 1200 Quell ST		
Order number for PURITY 1200	1033196	
Spare part to be used in combination with the suitable PURITY 1200 vessel lid (either with or without display unit) and the required PURITY 1200 filtration cartridge.		



Base with feet	Order number	
PURITY 450/600, blue	315757	● ●
PURITY 1200, black	315758	● ● ● ●



Handle set	Order number	
PURITY 450/600	321500	● ●
PURITY 1200	321400	● ● ● ●

- 2x mantle handle blue
- 2x lid handle blue (right and left)
- 8x screws for assembly



Flush valve		
Hose 550 mm grey synthetic material	550 mm	● ● ● ●
Order number	321700	

With stop valve.



Bend		
Order number	315648	● ● ● ●

3/4" - 3/4" for easy assembly and fixing of steep hoses.



Wall mounting bracket		
Dimensions (L/W/H)	212,2 x 271,5 x 453,5 mm	● ● ● ●
Order number for PURITY 450/600/1200	1015502	

Wall mounting bracket made of metal, stainless steel with chain for safe assembly of filters to the wall.



Gasket set I		
Order number	321800	● ● ● ●

- 3x flat gasket 3/4"
- 2x flat gasket 3/8"
- 2x O-rings (1" and 3/4" for inlet/outlet of filter head)

● PURITY Quell ST ● PURITY Steam ● PURITY Clean ● PURITY Clean Extra



BRITA Professional Filter Service App

The Filter Service App is your ideal assistant. This unique, comprehensive tool helps determine the right type and size of filter for your precise needs. It provides detailed installation guidance for service engineers, calculates when cartridges will need replacing - and has a wealth of other, innovative capabilities.

Download for free on



Or visit <https://professional.brita.net/app>

For more information please contact:

BRITA Water Filter Systems Ltd.

BRITA House | 9 Granville Way | Bicester | OX26 4JT | United Kingdom
Tel.: +44 844 742-4990 | Fax: +44 186 936-5962
UK001_clientservices@brita.net | www.brita.co.uk

BRITA Water Filter Systems Distributors Pty Ltd

Suite 2, Level 9, 123 Epping Road | Macquarie Park, NSW, 2113 | Australia
Tel.: +61 1300 955-021 | NZ: 0800 482-008
professional@brita.com.au | www.brita.com.au

Headquarters: BRITA SE

Heinz-Hankammer-Straße 1 | 65232 Taunusstein | Germany
Tel.: +49 6128 746-0 | Fax: +49 6128 746-5033
info@brita.net | www.brita.net